



R2000 Recirculator Specifications:



- > Factory set at 50 psi adjustable to 100 psi
- > 30,000 BTU
- > 115 VAC 50 / 60 Hz 1 phase
- > 230 VAC 50 / 60 Hz 1 ph
- > 230 / 190 VAC 50 / 60 Hz 3 ph
- > 460 / 380 VAC 50/60 Hz 3 ph
- > Dimensions: 23"L x 16"W x 19.5"H
- > 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
- > 8 foot power cord. (1 ph only)
- > Visible water level / water flow sight glass
- > Net weight: 68 lbs/31 kg
- > 6 gallon reservoir (15 gallon available)
- > 13.4 / 6.7 amp:60 Hz 1 ph
- > 2.6 / 1.3 amp:60 Hz 3 ph
- > Thermal overload
- > Foam packed for UPS shipment

R2000: Rotary GEAR Pump (only)

- > 3.5 gpm at 50 psi
- > Built in by-pass to tank
- > Rebuildable Pump (Repair Kit Product No. P2001)

System Features:

- > Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
- > All units are plumbed with copper tubing and reinforced hose.
- > New extended life pump.
- > Air flows into patented high efficiency radiator first for maximum efficiency.
- > No external plumbing is required because of closed loop water system.
- > A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
- > Water filter on pump inlet protects pump and extends pump life.