



R4000 Recirculator Specifications:



- > Factory set at 50 psi adjustable to 100 psi
- > 55,000 BTU
- > 115 / 230 VAC 50 / 60 Hz 1 ph
- > 230 / 190 VAC 50 / 60 Hz 3 ph
- > 460 / 380 VAC 50 / 60 Hz 3 ph
- > Dimensions: 36"L x 19.5"W x 35"H
- > 1/2" FPT SS Pipe - water in and out
- > Visible water level / water flow sight glass
- > Net weight: 170 lbs / 77 kg
- > 25 gallon reservoir
- > 20.4 / 10.2 amp : 60 Hz 1 ph
- > 5.4 / 2.7 amp: 60 Hz 3 ph

R4000: Rotary GEAR Pump (only)

- > 10.0 gpm at 50 psi
- > Built in by-pass to tank
- > Rebuildable Pump (Repair Kit No. P4018)

System Features:

- > Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
- > All units are plumbed with copper tubing and reinforced hose.
- > New extended life pump.
- > Air flows into patented high efficiency radiator first for maximum efficiency.
- > No external plumbing is required because of closed loop water system.
- > A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.